










## COLORED BODY GLAZED PORCELAIN

PHYSICAL PROPERTIES	TEST ASTM	NORTH AMERICAN STANDARD A137.1*	RESULTS FOR MATTE FINISH ONLY
 <b>Water absorption *</b>	C373	≤ 0.5%	COMPLY WITH ANSI A137.1
 <b>DCOF Average dynamic coefficient of friction</b>	BOT 3000 test	≥ 0.42	≥ 0.42
 <b>Resistance to freeze/thaw cycling *</b>	C1026	As reported	RESISTANT
 <b>Warpage (edge)</b>	C485	Warpage ± 0.4% or ± 0.05 in	COMPLY WITH ANSI A137.1
 <b>Warpage (diagonal)</b>	C485	Warpage ± 0.4% or ± 0.07 in	COMPLY WITH ANSI A137.1
 <b>Wedging</b>	C502	± 0.25% or ± 0.03 in	COMPLY WITH ANSI A137.1
 <b>Chemical resistance</b>	C650	As reported	RESISTANT
 <b>Breaking strength</b>	C648	250 lbf or greater	COMPLY WITH ANSI A137.1
 <b>Thickness</b>	C499	Range: 0.04 in	COMPLY WITH ANSI A137.1

\* Average values referred to our production and related to the matte finish of the product.

\*\* Shade Variation may vary by individual product. Please refer to catalog for specifics.

- Be sure to use tiles belonging to the same caliber.
- Test results are available on request.
- Tiles can be slippery when wet. We recommend to make sure that the surface is always dry.
- The information provided can be subject to change.

### Sizes /Thickness:

	Thickness [mm]
	8mm
<b>Nominal</b>	12x24
<b>Actual</b>	11.875x23.875