



Features Bedrock Beige FL01 Polished 24" x 48"

Beautiful depth, rich colors and a distinct, stone graphic are combined to perfection in the Fossilique Stone Porcelain™ series. Offered in large format field tile sizes, three unforgettable colors and two finishes, Polished and Lappato featuring Traction Enhance™ Technology, Fossilique Stone is an ideal series for traditional or contemporary design. A 3" Hexagon mosaic and a trim package that includes a 4" x 12" Bullnose, 6" x 12" Cove Base and 1" x 6" Cove Base Corner rounds out the series.

Bedrock Beige FL01



Crystal Gray FL02



Mineral Umber FL03





COLORS/FINISHES/SIZES/EDGE

| | |
|-----------------|---|
| Colors | Bedrock Beige FL01 Crystal Gray FL02 Mineral Umber FL03 |
| Finishes | Polished Traction Enhance™ Technology |
| Sizes | 24" x 48" 24" x 24" 12" x 24" 3" Hexagon Mosaic 4" x 12" Bullnose |
| Edge | Rectified |

TECHNICAL DATA

| | |
|-------------------------|---|
| Color Variation | V3 |
| DCOF | Polished – N/A TE Technology – ≥0.60 |
| Breaking Strength | ≥425 lbs. |
| MOHs | Polished – 4 - 5 TE Technology – 7 |
| Water Absorption | <0.5% |
| Chemical Resistance | Polished – Class A TE Technology – Class A |
| Abrasion Resistance | Class III |
| ANSI Classification | Polished – ID TE Technology – IW+ |
| Thermal Shock Resistant | Resistant |
| Frost Resistance | Resistant |

PACKAGING

| Size (Nominal) | 24" x 48" | 24" x 24" | 12" x 24" | 3" Hexagon | 4" x 12" Bullnose |
|---|---------------------|---------------------|--------------------|-------------------|-------------------|
| Size (Actual) | 23 9/16" x 47 5/16" | 23 9/16" x 23 9/16" | 11 3/4" x 23 9/16" | 10 1/4" x 11 3/4" | 4" x 11 3/4" |
| Pieces per Carton | 2 | 4 | 8 | 5 | 15 |
| Cartons per Pallet | 35 | 32 | 32 | 60 | 90 |
| SQFT per Carton | 15.49 | 15.46 | 15.38 | 4.20 | 4.64 |
| SQFT per Pallet | 542.20 | 494.70 | 492.20 | 252.00 | 417.60 |
| Weight per Carton (lbs.) | 67.00 | 67.00 | 66.80 | 18.00 | 22.00 |
| Thickness | 9.0mm | 9.0mm | 9.0mm | 9.0mm | 9.0mm |
| Minimum Recommended Grout Joint (Rectified) | 1/8" | 1/8" | 1/8" | 1/8" | 1/8" |