



# PreFormed Curb Overlay

DS-PREFCURBOVERLAY-070814

Data Sheets are subject to change without notice. For latest revision, visit our website at [www.finpan.com](http://www.finpan.com)

## 1. PRODUCT NAME

Fin Pan PreFormed Curb Overlay

## 2. MANUFACTURER

Fin Pan, Inc.

3255 Symmes Road

Hamilton, OH 45015

Telephone: 1-513-870-9200

Toll Free: 1-800-833-6444

Fax: 1-513-870-9606

Internet [www.finpan.com](http://www.finpan.com)

## 3. PRODUCT DESCRIPTION

PreFormed Curb Overlays are constructed of lightweight high-density expanded polystyrene wrapped with a fiberglass mesh and a liquid waterproof membrane finish. PreFormed Curb Overlays are quick to install and ready-to-tile.

**Materials:** Utility knife, modified thinset, cap nail fastener and polyurethane sealant.

### Advantages

- Lightweight and durable.
- fiberglass mesh wrap for added durability and tile adhesion.

### Uses

- Interior
- Showers
- Residential and commercial

### Suitable Substrates

- Traditional 2 x 4 curb stack and waterproof membrane.

### PreFormed Curb Overlay Model

PF-201/48" length

PF-202/96" length

### Shelf Life

- Factory sealed boxes are guaranteed to be of first quality for five (5) years if stored at temperatures  $>32^{\circ}\text{F}$  ( $0^{\circ}\text{C}$ ) and  $<100^{\circ}\text{F}$  ( $43^{\circ}\text{C}$ ).

### Limitations

- A sheet membrane must be installed under PreFormed Curb Overlays for total waterproofing.
- Substrate must meet industry standards.
- Mastics and silicones are never to be used.
- Don't expose to rubber solvents or ketones.
- Don't expose to sun or weather.

### Cautions

Consult MSDS for safety information.

## 4. TECHNICAL DATA

- Curb Overlays are rated to 40 psi.

## 5. INSTALLATION

**NOTE: Curb Overlay should be installed before installation of mortar bed and after installation of waterproof membrane.**

- Cut Curb Overlay to dimension of opening.
- Coat inside of Curb Overlay with modified thinset mortar and place over pan liner.
- Ensure the Curb Overlay is set firmly against curb structure.
- After leveling Curb Overlay, secure with cap nail fastener on outside of curb structure. **Do not compromise inside of curb structure with fasteners.**
- Apply a bead of polyurethane sealant where Curb Overlay meets the wall/jamb.

### Tile Installation Detail

- Install tile in accordance with the Tile Council of North America (TCNA) guidelines.

## 6. AVAILABILITY AND COST

### Availability

Fin Pan products are available worldwide.

### For Distributor information call:

Toll Free: 1-800-833-6444

Telephone: 1-513-870-9200

**Cost:** Contact a Fin Pan Distributor in your area

## 7. WARRANTY

Contact Fin Pan

## 8. MAINTENANCE

PreFormed Curb Overlays require no maintenance.

## 9. TECHNICAL SERVICES

### Technical Assistance

Information is available by calling Fin Pan Monday thru Friday from 8:00 AM to 5:00 PM EST.

### Technical and Safety Literature

Please visit our website at [www.finpan.com](http://www.finpan.com).

## 10. FILING SYSTEM

Information is available at [www.finpan.com](http://www.finpan.com).